



CONTOUR FRACTAL DIMENSION ANALYSIS USING SQUARE-BOX ROI EXTRACTION APPROACH WITH CONVOLUTION NEURAL NETWORK CLASSIFIER FOR PALMPRINT RECOGNITION SYSTEM

Abirami B* Krishnaveni K**

*Research Scholar, Research Department of Computer Science, Sri S.Ramasamy Naidu Memorial College, Affiliated with Madurai Kamaraj University, Sattur - 626203, Virudhunagar District, Tamilnadu, India.

**Associate Professor, Research Department of Computer Science, Sri S.Ramasamy Naidu Memorial College, Affiliated with Madurai Kamaraj University, Sattur - 626203, Virudhunagar District, Tamilnadu, India.

Abstract

Contour Fractal Dimension Analysis using Square-Box ROI Extraction Approach with Convolution Neural Network Classifier for Palmprint Recognition System (CFDCNNNet) is proposed. To bring about the originality, Contour Fractal Dimension (CFD) feature extraction approach and a Convolution Neural Network (CNNNet) classifier approach are employed. To impart the novelty the CFD feature extraction approach, Two Dimensional-Palmprint Region of Interest (2D-PROI) is captured from five different datasets using Square-Box ROI Extraction approach and point out all the edges/contours of 2D-PROI image (CPI) using Canny edge detection algorithm and then estimate the Fractal Dimension (FD) values using Box-Counting algorithm to create a distinctive feature vector. Classify this feature vector using Convolution Neural Network (CNNNet) classifier approach to identify the authorized person at a higher accuracy rate. This research explores on five different datasets such as CASIA, IITD, BMPD, SMPD and multi-spectral 2D-PROI image databases. The CFDCNNNet System model has been determined the authentication accuracy of different datasets with 98.66% of authentication accuracy.

Keywords: Palm print Recognition System – Square-Box ROI extraction approach – Contour Fractal Dimension – Box-Counting – Fractal Dimension - Convolution Neural Network Classifier.

Introduction

Due to their distinctiveness and security, biometric recognition systems are widely used in many applications. Due to its stability, feature-richness, dependability, and improved user acceptability, hand-based person recognition has gained significant impetus in recent years. Now-a-days, the authentication technology is preferred the biometric sensing. Biometric systems can be performed in either unimodal or multimodal system[2]. Unimodal biometric systems are facing the issues of spoof attacks, subpar sample quality, intra-class variability, and user acceptance plague [3]. The vast majority of these issues can be avoided by fusing data from many modalities [4].

Principle lines, valleys, wrinkles, and ridges on the palmar surface, are distinguishing the characteristics of palm print to perform the authentication [5]. In recent years, several Convolution Neural Network (CNN) approaches have been presented in the palm print recognition system [6]. An fascinating parameter to describe the roughness of an image is the fractal dimension[7]. It is able to be applied for information such as texture segmentation, three-dimensional (3D) shape estimate, and more[8]. [9] In this study, we employ a highly complex and cutting-edge technique of the fractal approach, to extract the characteristics of the palm print texture information. This method has gained the popularity recently and is seen to be a hot topic for study in the field of image processing.



The fractal dimension (FD) technique is regarded for analyzing the texture representation, textual identification, palmprint and signature recognition [10] [11]. [12] This paper has proven the fractal-based feature extraction methodology to be the most acceptable method. Mandelbrot developed fractal geometry in 1983 to define fractals as collections of self-identical objects. The fractal dimension, which indicates the pattern changes characteristic at various scales, is a ratio that characterizes the asymmetry and the complexity of stochastic models [13]. The most advanced and user-friendly method to calculate the image's fractal dimension is the box-counting algorithm [14].

[15] is shown that a better palmprint identification rate obtained using the deep learning approach. Machine learning algorithms use prior topic knowledge to more accurately predict the outcome. However, large datasets are not properly learnt by machine learning algorithms, resulting in lack of interpretability and clarity in decision-making[16]. In the medical and biometric fields, deep learning on large datasets is most effective, and its improved algorithms train the datasets more quickly and correctly [17].

Our proposed research constructs a novel CFDCNN_{Net} classifier technique for the palmprint recognition system. To identify the different characteristics, it computes the fractal dimension values of the contours 2D-PROI image using canny edge detection algorithm. The input 2D-PROI image can be cropped using the novel square box ROI extraction algorithm. Proposed methodology of this research is discussed in the section 3. Classification level, and conclusion are described in section 3 and 6.

2 Proposed Methodology

Data acquiring phase, Pre-processing phase, Feature extraction phase, and Classification phase are the four vital phases of proposed palmprint recognition system (CFDCNN_{Net}) [1]. The identification and authentication processes of CFDCNN_{Net} are illustrated in Fig.1, and Fig. 2.




Fig.1. Block Diagram of CFDCNN_{Net} Identification Process




Fig.2. Block Diagram of CFDCNN_{Net} Authentication Process

2.1 Data Acquiring

This research is scrutinized the palmprint images from various palm hand image datasets. Different datasets are derived from Indian Institutes of Information Technology (IIT) database, Birjand University Mobile Palmprint database (BMPD), CASIA palm database, Sapienza University mobile palmprint database (SMPD) database, and POLYU database.

The hand images took from 230 users of IIT Delhi students in New Delhi, India. All are stored in bitmap (*.bmp) format. Seven images of each subject, with their left and right hands in various hand poses are taken. It is shown in Fig.3.a.

5,502 palmprint images from 312 subjects are stored in the CASIA palmprint image database. Left and right palmprint images captured for each subject. It is shown in Fig.3.d.

8000 2D-PROI segmented and normalized BMP image files are accessed at the biometric research center (UGC/CRC) in POLYU, Hong Kong. 400 volunteers' left and right hands' palms are stored in two separate sections. Each section has 10 images of each palm and some of these sample 2D-PROI images are shown in Fig. 4.

In the Birjand University Mobile Palmprint Database (BMPD), Left and right hands of 41 Iranian women images were collected. Totally, 1640 images are collected in two sessions with the interval of two weeks. Sample images of BMPD are shown in Fig.3.c.



110 international students' right hands images are taken from Sapienza and Tor Vergata universities in Rome. In this database, the distance between the palm and the smartphone is adjusted so that the best image quality can be obtained. It is shown in Fig.3.d.




Fig.3. a. IIT Dataset Image, b. BMPD Dataset Image, c. SMPD Dataset Image, and d. CASIA Dataset Image.




Fig.4. Sample 2D-PROI images from biometric research center (UGC/CRC) in POLYU, Hong Kong.

2.2 Pre-processing

The input image is pre-processed to make the input image quality in a well-qualified manner. It can be accomplished by performing the following steps: 1. Gray-scale conversion of image, 2. Detach the noise of data in the image, 3. Extract the 2D-PROI area using square-box ROI extraction approach to obtain the unique feature values and labeled as 2D-PROI image, 4. Rise up the spatial intensity level of the image to highlight the tiny creases, lines and ridges of palmprint, which are depicted in Fig. 5.a, 5.b, 5.c, 5.d, and 5.e. Finally, the resultant pre-processed image is labeled as Pre-processed 2D-PROI Image (CP^I).

Square-Box 2D-PROI Extraction Approach

The procedure adapted in the Square-box 2D-PROI extraction approach:

- a. Separate the palm hand image from the background image using binary conversion.
- b. Find out the perimeter pixels of an object to grasp the border boundaries of the palm image.
- c. Marked the center region of the palm image (CI) using centroid property of Regionprops() function.
- d. Extract the center point of palmar surface (CP) using the estimation of mid-point pixels value between the CI points and the endpoint pixel values of the palm's wrist at Y-axis, which is marked as WP. That is shown in Fig.6.
- e. Pixel points of Left End Point (LEP) are attained at the x-axis of CP points, which is revealed in Fig.6.
- f. Create the straight horizontal line between the end points of CP and LEP pixel values and set that length of the straight line value as the values of rectangular box's width and height. It produced the square-box area. Finally, cropped the image is kept inside the square-box area and labeled it as 2D-PROI image.

After attained the 2D-PROI image, canny edge detection algorithm is applied on 2D-PROI image to produce the contour 2D-PROI image and marked it as CP^I. It is shown as Fig.5.e.




Fig.5. a. IIT Dataset Input Image, b. Smoothen Input Image, c. ROI Extraction using Square-box ROI Extraction Approach, d. Cropped 2D-ROI image, e. Contour 2D-PROI Image CP^I







Fig.6. Pictorial Representation of Square-box 2D-PROI Extraction Approach



(a)



(b)



(c)





Fig.9. CNN_{Net} Learning Progress chart for Various Datasets Images, a. CASIA Dataset Images, b. IIT Datasets, c. BMPD Datasets, d. SMPD Datasets, e. PolyU Datasets.

Performance of our proposed system (CFDCNN_{NET}) is determined using confusion matrix parameters such as False Negative Rate(FNR), False Positive Rate(FPR), True Positive Rate(TPR), and Correct Positive Rate (CPR), Precision, and Specificity. To measure the parameter values of the confusion matrix, the predicted values (True Positive (TP), True Negative (TN), False Positive (FP), and False Negative(FN)) are in particular computed. These values are collected during the testing phase, when a set of the testing template is compared to a set of the trained template and a count is made of the number of testing datasets that are successfully matched or not. Using (4), (5), (6), (7), and (8), these anticipated values are substituted in the confusion matrix parameters.



$$\text{True Positive Rate (TPR)} = \frac{TP}{TP + FN} \quad (4)$$

$$\text{False Positive Rate(FPR)} = \frac{FP}{FP + TN} \quad (5)$$

$$\text{CPR} = \frac{TP + TN}{TP + FN + TN + FP} \quad (6)$$

$$\text{Precision} = \frac{TP}{TP + FP} \quad (7)$$

$$\text{Specificity} = \frac{TN}{TN + FP} \quad (8)$$

The accuracy rate of recognition in every testing datasets is shown in Fig. 10. The suggested (CFDCNN_{NET}) system is executed successfully in its proposed feature extraction on various datasets which is disclosed by examining other current approaches as well as its recognition accuracy rate. Our proposed system (CFDCNN_{NET}) shows the best result accuracy rate in all datasets.

Table 2. Predicted Values of Confusion Matrix Parameters for five different testing templates

300 Testing samples from Five Different Testing Templates	TP	TN	FP	FN	FNR	FPR	TPR	CPR
CASIA Datasets	291	2	2	5	0.0168%	0.5%	0.9831%	0.9766%
IITD Datasets	288	6	1	5	0.0170%	0.1428%	0.98293%	0.98%
BMPD Datasets	290	5	3	2	0.0068%	0.375%	0.9931%	0.9833%
SMPD Datasets	292	2	1	5	0.0168%	0.3333%	0.9831%	0.98%
PolyU Datasets	292	4	2	2	0.0068%	0.3333%	0.9931%	0.9866%

Performance of Proposed System




Fig.10. Chart Representation of CFDCNN_{Net} System Classification Performance



3 .Discussion

The goal of our research is a Contour Fractal Dimension Analysis utilising Square-Box ROI extraction approach with Convolution Neural Network Classifier (CFDCNN_{Net}) is suggested to achieve a high authentication recognized accuracy in PRS. That can be achieved uniquely with 98.66% correct authentication accuracy of different palm hand images from various datasets, which is shown in Fig.10. And Table.3 exposes the performance analysis of various approaches used in PRS with the proposed approach (CFDCNN_{Net}) and divulges the achievement of best with 98.66% of authentication recognized accuracy in this research.

Table.3. Performance Analysis of Various Approaches along with the Proposed Approach

S.No.	Approaches	Accuracy Rate	Year
1.	Box Counting +Mass Radius+ Cumulative intersection+KNN+SVM classifier[18]	96.35% for CASIA-Palmprint dataset and 95.98% for IITD-Touchless-Palmprint dataset.	2016
2.	TAFD-BC[19]	96% of PolyU 2D Palmprint database	2017
3.	The Multi-fractal dimension features using the Canonical Correlation Analysis (CCA) incorporating the Linear Discriminant Analysis (LDA) [20]	96.02% for PolyU-Palmprint database and 97.00% for CASIA-Palmprint database.	2017
4	DSL+DCFPR[21]	98% of authentication accuracy.	2022
5	DSL+RCFD[22]	98% of authentication accuracy.	2022
6	Proposed System	98.66% of accuracy	---

Conclusion

This research explores the authentication control of PRS using the novel system CFDCNN_{Net} with different dataset images. This research experienced on five different datasets, on each 300 palm hand images are taken and make it as 2D-PROI using the Square-Box ROI extraction approach and formed the CP^I image using the Canny edge detection algorithm. A distinctive feature vector of CP^I is created as testing and training templates using the estimation of Fractal Dimension (FD) values using the Box-Counting algorithm. At ultimate, identification and authentication process can be performed and achieved 98.66% accuracy of authentication rate using CFDCNN_{Net} classifier approach. Although, this research does not obtain the 100% accuracy of authentication recognized rate due to the presence of



similarity in the FD values in several dataset images. In the future work, it will be carry out by applying the hybrid approach of model based feature extraction approach in PRS that tends to make more distinctive feature values without similarity values.

References

1. Attia, A., Mazaa, S., Akhtar, Z., & ,Chahir, Y. (2022). Deep learning-driven palmprint and finger knuckle pattern-based multimodal Person recognition system. *Multimedia Tools and Applications*, 81(8), 10961-10980.
2. 2) Joseph, T., Kalaiselvan, S.A., Aswathy, S.U., Radhakrishnan, R., Shamna, A.R., (2020). A multimodal biometric authentication scheme based on feature fusion for improving security in cloud environment. *J Ambient Intell Human Comput*.
3. Modak, S.K.S., Jha V.K., (2019). Multibiometric fusion strategy and its applications: a review. *Inf Fusion* 49:174–204.
4. Tistarelli, M., Schouten, B. (2011). Biometrics in ambient intelligence. *J Ambient Intell Human Comput* 2(2):113–126.
5. Zhao, S., Wu, J., Fei, L., Zhang, B., & Zhao, P. (2022). Double-cohesion learning based multiview and discriminant palmprint recognition. *Information Fusion*, 83, 96-109.
6. Jia, W., Ren, Q., Zhao, Y., Li, S., Min, H., & Chen, Y. (2022). EEPNet: An efficient and effective convolutional neural network for palmprint recognition. *Pattern Recognition Letters*, 159, 140-149.
7. Panigrahy, C., Seal, A., Mahato, N. K., &Bhattacharjee, D. (2019). Differential box counting methods for estimating fractal dimension of gray-scale images: A survey. *Chaos, Solitons & Fractals*, 126, 178-202.
8. Balasubramanian, A., & Krishnasamy, K. (2022, September). A Novel Deep Supervised Contour Fractal Dimension Analysis Model. In *International Conference on Innovative Computing and Communications: Proceedings of ICICC 2022, Volume 1* (pp. 409-424). Singapore: Springer Nature Singapore.
9. Mokni, R., & Kherallah, M. (2016). Palmprint recognition through the fractal dimension estimation for texture analysis. *International Journal of Biometrics*, 8(3-4), 254-274.
10. Raouia, M., Hassen, D., and Monji, K., (2020). Deep-Analysis of Palmprint Representation based on Correlation Concept for Human Biometrics identification, *International Journal of Digital Crime and Forensics*, pp. halshs-03147087.
11. Shi, X., Cheng, H.D., Hu, L., Ju, W., and Tian, J., (2010). Detection and Classification of Masses in Breast Ultrasound Images, *Digital Signal Process*, vol. 20, no. 3, pp. 824-836.
12. Ivanovici, M., and Richard, N., (2011). Fractal Dimension of Color Fractal Images, *IEEE Transactons On Image Processing*, vol. 20, no. 1.
13. Yui, L., Zhang, D., Wang, K., and Yang, W., (2005). Coarse iris classification using box-counting to estimate fractal dimensions, *Pattern Recognition Society (Elsevier)*, vol. 38, p. 1791 – 1798.
14. Kisan, S., Mishra, S., Bhattacharjee, G., and Bansal, R., (2018). Analytical Study on Fractal Dimension- A Review, *International Conference on Recent Innovations in Electrical, Electronics & Communication Engineering (ICRIEECE)*, Bhubaneswar, India.
15. Dandan, Z., Xin, P., Xiaoling, L., and Xiaojing, G., (2015). Palmprint Recognition Based on Deep Learning, in *ICWMMN Proceedings*.
16. LeCun, Y., Bengio, Y., and Hinton, G., (2019). Deep learning, *Nature*, vol. 521, pp. 436-444.
17. Li, S., L, M., D, R., J. H., Eugene, F., Russell, M., and Weiva, S., (2019), Deep Learning to Improve Breast Cancer Detection on Screening Mammography, *Scientific Reports* , vol. 9, no.



12495.

18. Mokni, R., & Kherallah, M. (2016, October). Novel palmprint biometric system combining several fractal methods for texture information extraction. In 2016 IEEE International Conference on Systems, Man, and Cybernetics (SMC) (pp. 002267-002272). IEEE.
19. Mokni, R., & Kherallah, M. (2016). Palmprint recognition through the fractal dimension estimation for texture analysis. *International Journal of Biometrics*, 8(3-4), 254-274.
20. Mokni, R., Drira, H., & Kherallah, M. (2017, October). Fusing multi-techniques based on LDA-CCA and their application in palmprint identification system. In 2017 IEEE/ACS 14th International Conference on Computer Systems and Applications (AICCSA) (pp. 350-357). IEEE.
21. Balasubramanian, A., & Krishnasamy, K. (2022). A Novel Deep Supervised Contour Fractal Dimension Analysis Model for Palmprint Recognition. *Journal of Algebraic Statistics*, 13(3), 1074-1083.
22. Balasubramanian, A., & Krishnasamy, K. (2022, September). A Novel Deep Supervised Contour Fractal Dimension Analysis Model. In *International Conference on Innovative Computing and Communications: Proceedings of ICICC 2022, Volume 1* (pp. 409-424). Singapore: Springer Nature Singapore.